ON DEMAND MACHINERY

PATTERN GLUING MADE SIMPLE!

Stenciler

The ODM Stencil Gluing Machine applies a pattern of adhesive or overall coating to photo album pages, envelopes, sample cards, display easels, pressure sensitive box blanks, skin pack cards or any product requiring a precision coating of adhesive in a pattern. The machine handles latex and self-stick adhesives, and can be supplemented with a drying conveyor, perforating wheels, folding plows, stacking table or automatic feeder. The standard size machine will handle a maximum product size of 18" wide by 18" long. High production speeds between 3,000 and 3,500 per hour can be easily achieved.

STANDARD FEATURES:

- The in-feed chains are constructed from standard roller chain and can easily be adjusted on the fly.
- The Stencil Gluing Machine comes equipped with an air powered impression cylinder that is activated with an electric eye.
- A stencil template registration system enables patterns to be re-used.
- The simplified glue pot design is user-friendly and can be easily removed from the machine for a fast clean up.
- A cylinder pressure adjustment can be made in seconds.
- Glue pattern registration system outputs a precision placement of adhesive on the sheet.
- Machine incorporates ball bearings throughout, making it virtually maintenance free.
- Custom automatic feeder available upon request.

Finished Samples:







Coin Folder Book



Children's Board Books

Stenciler



Coin Holder Book





N R GL G M A G P Ε A N


Stenciler Gluing Machine Offers Outstanding Value, Quality, and Performance!


SPECIFICATIONS & TECHNICAL DATA:	STENCILER MODEL	STANDARD EQUIPMENT for STENCILER PATTERN GLUING MACHINE INCLUDE:
Maximum Page Size:	18" x 18"	• In-feed chains can be adjusted on the fly.
Minimum Page Size:	5" x 5"	• Stencil template registration patterns can be reused.
Output (per hour):	up to 4500 cycles	• User friendly glue pot can be removed for fast clean up.
Floor Space:	30" x 60"	 Easily adjustable glue pattern registration system
Net Weight:	650 lbs.	outputs a precision placement of adhesive on a sheet.
Power Required:	115 Volt, 15 Amps	 Impression cylinder controlled by an electric eye.
	60 Cycle, 1 HP	• Easy to adjust cylinder pressure.
Also Required:	Air Line	Virtually maintenance free.
		• Custom automatic feeder available upon request.


DIMENSIONS: FRONT VIEW

SIDE VIEW

OVERHEAD VIEW







Finished Samples:



150 Broadway, Elizabeth, NJ 07206 • Tel: 908-351-6906 • Fax: 908-351-7156 • www.ODMachinery.com